

# CMT-7404 DATASHEET

Revision: 1.5

10-Dec-23

(Last Modified Date)

## High-Temperature, Hex Inverter

---

### General Description

The CMT-7404 contains six independent inverter, performing the Boolean function :

$$Y = \bar{A}$$

This circuit is fabricated using a CMOS SOI process, assuring latchup-free operation for all supply and temperature conditions.

The CMT-7404 can operate with supply voltages from 3.3 to 5V ( $\pm 10\%$ ).

The CMT-7404 uses internal metal lines presenting extremely high immunity to electromigration, improving product lifetime by a factor of 10, compared to the case where aluminum metallization is used.

### Features


- Qualified from -55 to +175°C (T<sub>j</sub>)
- 3.3 to 5V ( $\pm 10\%$ ) supply voltages
- Latchup-free at any supply and temperature condition
- Validated at 175°C for 20000 hours (and still on-going)
- Available in plastic SOIC16 standard package
- Improved internal metallization for extended reliability

### Applications

- Well logging,
- Automotive, Aeronautics & Aerospace
- Harsh Environments

---

### Package and Pin Configuration



Pin	Symbol	Description
1	IN1	Input of inverter number 1
2	OUT1	Output of inverter number 1
3	IN2	Input of inverter number 2
4	OUT2	Output of inverter number 2
5	IN3	Input of inverter number 3
6	OUT3	Output of inverter number 3
7	GND	Circuit core ground terminal.
8	N.C.	No connected terminal
9	N.C.	No connected terminal
10	IN4	Input of inverter number 4
11	OUT4	Output of inverter number 4
12	IN5	Input of inverter number 5
13	OUT5	Output of inverter number 5
14	IN6	Input of inverter number 6
15	OUT6	Output of inverter number 6
16	VDD	Circuit core power supply terminal.

### Function Table

INPUT	OUTPUT
A	Y
L	H
H	L

### Function and Logical Diagrams




Figure 1. CMT-7404: simplified block diagram.

**Absolute Maximum Ratings**

Supply Voltage $V_{DD}$ to GND	-0.5 to 6.0V
Voltage on any Pin to GND	-0.5 to $V_{DD}+0.5V$

**Operating Conditions**

Supply Voltage $V_{DD}$ to GND	3.3V to 5V ( $\pm 10\%$ )
Junction temperature	-55°C to +175°C

**ESD Rating (expected)**

Human Body Model	1kV
------------------	-----

**DC Electrical Characteristics**

Unless otherwise stated:  $T_i=25^\circ C$ . **Bold underlined** figures indicate values valid over the whole temperature range (-55°C <  $T_j$  < +175°C).

Parameter	Condition	Min	Typ	Max	Units
Supply voltage $V_{DD}$		3.3	5V		V
Quiescent current $I_{DD}$	$V_{DD} = 3.3V, T_j=-55^\circ C$			4	nA
	$V_{DD} = 5V, T_j=-55^\circ C$			6	
	$V_{DD} = 3.3V, T_j=175^\circ C$			<b><u>928</u></b>	
	$V_{DD} = 5V, T_j=175^\circ C$			<b><u>229</u></b>	
Minimum HIGH level output voltage $V_{OH}$	$V_{DD} = 3.3V, I_{OH}<2mA$ (source)	<b><u>2.46</u></b>			V
	$V_{DD} = 5V, I_{OH}<4mA$ (source)	<b><u>4.47</u></b>			
Maximum LOW level output voltage $V_{OL}$	$V_{DD} = 3.3V, I_{OL}<2mA$ (sink)			<b><u>0.41</u></b>	V
	$V_{DD} = 5V, I_{OL}<4mA$ (sink)			<b><u>0.59</u></b>	
Minimum HIGH level input voltage $V_{IH}$	$V_{DD} = 3.3V$	<b><u>2.2</u></b>			V
	$V_{DD} = 5V$	<b><u>3.3</u></b>			
Maximum LOW level input voltage $V_{IL}$	$V_{DD} = 3.3V$			<b><u>1.5</u></b>	V
	$V_{DD} = 5V$			<b><u>2.2</u></b>	

## AC Electrical Characteristics

Unless otherwise stated: VDD=5V,  $T_j=25^\circ\text{C}$ . **Bold underlined** figures indicate values valid over the whole temperature range ( $-55^\circ\text{C} < T_j < +175^\circ\text{C}$ ).

Parameter	Condition	Temperature	Min	Typ	Max	Units
Propagation delay time from A to Y <b><u>t<sub>PHL</sub></u></b>	$C_L=50\text{pF}$	$T_j=-55^\circ\text{C}$		7.2	9.5	ns
		$T_j=25^\circ\text{C}$		8.7	11.9	
		$T_j=175^\circ\text{C}$		12	17	
Propagation delay time from A to Y <b><u>t<sub>PLH</sub></u></b>	$C_L=50\text{pF}$	$T_j=-55^\circ\text{C}$		6.3	8.8	ns
		$T_j=25^\circ\text{C}$		7.9	11.2	
		$T_j=175^\circ\text{C}$		10.8	15.8	
Output transition time High to Low <b><u>t<sub>THL</sub></u></b>	$C_L=50\text{pF}$	$T_j=-55^\circ\text{C}$		6.6	8.4	ns
		$T_j=25^\circ\text{C}$		8.1	10.7	
		$T_j=175^\circ\text{C}$		11.8	16	
Output transition time Low to High <b><u>t<sub>TLH</sub></u></b>	$C_L=50\text{pF}$	$T_j=-55^\circ\text{C}$		5.2	7.5	ns
		$T_j=25^\circ\text{C}$		6.9	9.9	
		$T_j=175^\circ\text{C}$		9.8	13.8	

## AC Electrical Characteristics (cntd)

Unless otherwise stated: VDD=3.3V,  $T_j=25^\circ\text{C}$ . **Bold underlined** figures indicate values valid over the whole temperature range ( $-55^\circ\text{C} < T_j < +175^\circ\text{C}$ ).

Parameter	Condition	Temperature	Min	Typ	Max	Units
Propagation delay time from A or B to Y $t_{PHL}$	$C_L=50\text{pF}$	$T_j=-55^\circ\text{C}$		14	22.1	ns
		$T_j=25^\circ\text{C}$		16.5	26.6	
		$T_j=175^\circ\text{C}$		21.5	34.4	
Propagation delay time from A or B to Y $t_{PLH}$	$C_L=50\text{pF}$	$T_j=-55^\circ\text{C}$		12.3	20.1	ns
		$T_j=25^\circ\text{C}$		15	24.4	
		$T_j=175^\circ\text{C}$		19.4	31.2	
Output transition time High to Low $t_{THL}$	$C_L=50\text{pF}$	$T_j=-55^\circ\text{C}$		10.7	17	ns
		$T_j=25^\circ\text{C}$		13	21.5	
		$T_j=175^\circ\text{C}$		18	29.5	
Output transition time Low to High $t_{TLH}$	$C_L=50\text{pF}$	$T_j=-55^\circ\text{C}$		8	14.3	ns
		$T_j=25^\circ\text{C}$		10.2	16.8	
		$T_j=175^\circ\text{C}$		13.5	21	

## AC Waveforms





Figure 2. AC Waveforms

## Ordering Information

Ordering Reference	Package	Temperature Range	Marking
CMT-7404-PSOIC16-T	Plastic SOIC16	-55°C to +175°C	CMT-7404

## Package Dimensions



Drawing PSOIC16 (mm)

## Contact & Ordering

CISOID S.A.

Headquarters and contact EMEA:	CISOID S.A. – Rue Francqui, 11 – 1435 Mont Saint Guibert - Belgium T : +32 10 48 92 10 - F: +32 10 88 98 75 Email: <a href="mailto:sales@cisoid.com">sales@cisoid.com</a>
Sales Representatives:	Visit our website: <a href="http://www.cisoid.com/contact">http://www.cisoid.com/contact</a>

## Disclaimer

Neither CISOID, nor any of its directors, employees or affiliates make any representations or extend any warranties of any kind, either express or implied, including but not limited to warranties of merchantability, fitness for a particular purpose, and the absence of latent or other defects, whether or not discoverable. In no event shall CISOID, its directors, employees and affiliates be liable for direct, indirect, special, incidental or consequential damages of any kind arising out of the use of its circuits and their documentation, even if they have been advised of the possibility of such a damage. The circuits are provided "as is". CISOID has no obligation to provide maintenance, support, updates, or modifications.